

DKF 294 ODIN gen2

TAKTON



Benefits:

- Entry level LED luminaire with lowest initial capital investment
- Slim aesthetic design
- Essential reducing energy consumption with Philips driver
- Reliable quality
- Energy efficiency up to 150 lm/W
- Asymmetrical and symmetrical optics

TYPE	Product type: DKF 294
ELECTRICAL PARAMETERS	Driver efficiency nominal: > 0,92
	Driver failure ratio: < 10% at 100 000 hours
	Driver type: Built in PHILIPS Xitanium outdoor driver or Meanwell depends on type
	Electrical isolation class IEC: Safety class I as a standard, II on request
	Input Frequency: 50-60 Hz
	LED current ripple %: < (4-30) depends on type
	Mains voltage index: 220-240 V / 50-60 Hz
	Nominal input voltage range: 202..254 or 198...264, depends on type
	Power factor nominal: up to 0.98
	Power range: 123-181W depending on type
	Surge protection: 4/6 kV

LIGHTING PERFORMANCE

CCT:

3000K, 4000K, 5700K

Color rendering index, CRI:

> 70

Initial color shift, SDCM:

< 5

Light distribution:

Asymmetric for areas ASWD,
Symmetric RS48, Symmetric RS23

Light source:

Modules with OSRAM LED chips

LOR:

up to 0,94

Luminaire lumen output range, lm:

18200....26700 Lm depending on
type

Photobiological safety:

RG1

Type of optic:

Low ageing PMMA lenses by LEDIL

CONSTRUCTION AND MATERIALS

Dimensions LxWxH:

532x347x68

Effective protected area:

At horizontal position 0.052

Housing colour:

Grey

Housing material:

Housing: high-pressure, die-cast
aluminium powder coated, no plastic
parts

Impact resistance:

IK08

Ingress protection:

IP66

Installation options:

U-shape mounting bracket fixed with
standard bolts and nuts. No need
open for electrical connection

Optical cover:

Extra clear toughened flat glass

Windage area:

no more 0,185sq.m above/below
and 0,036sq.m side position

DKF 294 ODIN gen2

TAKTON

OPERATION AND MAINTENANCE

Electrical connection:

0.4m cable as standard

Maintenance:

Opening with screw, LED modules are non-replaceable and can be replaced by manufacturer only, no internal cleaning required

Maintenance of lumen output:

100 000 hours – L90B10

Application:

- Billboards/advertising lighting
- Landscape features
- Security and amenity lighting
- General lighting

MARKING AND APPROVALS

CE mark:

CE marked

ROHS mark:

ROHS compliant

PRODUCT FAMILY RANGE

DKF 294 ODIN gen2

TAKTON

Code	Type	LED current, A	Initial luminous flux, lm	Power, W	L90/B10, Hours	Weight, kg
600151431319	DKF294 LED182123W 740 I ASWD IC0	0,7	18200	123	50 000	8,5
60015143132	DKF294 LED189123W 740 I RS48 IC0	0,7	18900	123	50 000	8,5
600151431311	DKF294 LED214140W 740 I RS48 IC0	0,7	21400	140	50 000	8,5
600151431312	DKF294 LED206140W 740 I ASWD IC0	0,7	20600	140	50 000	8,5
600151431313	DKF294 LED267172W 740 I RS48 IC0	0,7	26700	172	50 000	8,5
600151431314	DKF294 LED258172W 740 I ASWD IC0	0,7	25800	172	50 000	8,5
	Eco Version					
600151431804	DKF294 LED260189W I 740 ASWD	1,05	26000	189	30 000	8,5
600151431807	DKF294 LED267189W I 740 RS48	1,05	26700	189	30 000	8,5
600151431812	DKF294 LED230190W I 740 RS23	1,05	24300	190	30 000	8,5