

2350 LED

LED surface-mounted luminaire

- Adjustable light colour and luminous intensity
- VDU workstation-compliant (UGR < 19)
- Wireless Connect types

The 2350G4 is the tried-and-tested surface-mounted luminaire in the twenty3 portfolio. A square and two elongated designs make it the ideal lighting solution for offices, foyers and educational institutions, for example. Adjustable light colour and luminous intensity make them particularly flexible. Wireless Connect and DALI types enable use with lighting management systems. This way you will master the job!

Why you'll get the job done with the 2350 G4 surface-mounted luminaire

- Flexible setting of luminaire luminous flux due to multilumen
- Thanks to Multicolour, two light colours in one luminaire.
- 1:1 replacement of conventional luminaires during refurbishment.
- Optimised luminaire design for easy installation: separate frame and light unit.
- Pleasant light effect due to uniform illumination
- Suitable for VDU workstations (UGR < 19).
- High efficiency (up to 130 lm/W).
- Reliable service life (50,000 h, L80).

2350 LED at a glance

Dimensions	602 x 602 x 50 mm, 1.202 x 302 x 50 mm, 1.502 x 302 x 50 mm
Luminaire luminous flux	Multilumen: 3.600 / 2.900 lm, 4.000 / 3.000 lm, 6.000 / 4.000 lm
Colour Temperature	Multicolour: 3.000 K / 4.000 K
Protection rating, Safety class	IP20/ IK02, Schutzklasse I
Weight	2,8 kg, 3,4 kg, 4,2 kg
Lightmanagement	LiveLinkReady (ETDD), Wireless Connect (ETWD)
Service life	50.000 h (L80)

2350 LED

Product reference	TOC	Luminous flux [lm]	Connected load [W]	Colour temperature [K]	Dimensions [mm]
Multicolour + Multilumen					
2350 G4 D PW19 36/29/ML-8MC ET	8537240	2900 - 3600 lm	22 - 28 W	3000 - 4000 K	602 x 602 x 50 mm
2350 G4 D2 PW19 40/30/ML-8MC ET	8537340	3000 - 4000 lm	23 - 31 W	3000 - 4000 K	1202 x 302 x 50 mm
2350 G4 D3 PW19 60/40/ML-8MC ET	8537540	4000 - 6000 lm	33 - 46 W	3000 - 4000 K	1502 x 302 x 50 mm
Multicolour DALI					
2350 G4 D2 PW19 4000-8MC ETDD	8537451	3800 - 4000 lm	33 W	3000 - 4000 K	1202 x 302 x 50 mm
2350 G4 D3 PW19 6000-8MC ETDD	8537651	5700 - 6000 lm	49 W	3000 - 4000 K	1502 x 302 x 50 mm
Multicolour Wireless Connect					
2350 G4 D PW19 3600-8MC ETWD	8537965	3400 - 3600 lm	33 W	3000 - 4000 K	602 x 602 x 50 mm
2350 G4 D2 PW19 4000-8MC ETWD	8537765	3800 - 4000 lm	36 W	3000 - 4000 K	1202 x 302 x 50 mm
2350 G4 D3 PW19 4400-8MC ETWD	8537865	4100 - 4400 lm	40 W	3000 - 4000 K	1502 x 302 x 50 mm