

Sensor-switched LED indoor light

RS PRO P3 S

Neutral white

EAN 4007841 056117

Article number 056117



Light source not exchangeable



Control gear not exchangeable

Function description

Circular classic. Perfect shape. Perfect efficiency. The perfect switched indoor light. The RS PRO P3 S integrates harmoniously into corridors, hallways and stairwells. It combines timeless design and extremely easy installation with pioneering technology and unbeatable efficiency. As many as ten lights can be interconnected by cable. Output: 18,4 W with 2188 lm, 4000 K.

Technical specifications

Dimensions (Ø x H)	400 x 142 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Output	18,4 W
Interconnection	Yes
Lichtstrom Gesamtprodukt	2188 lm
Gesamtprodukt Effizienz	119 lm/W
Colour temperature	4000 K
Colour Rendering Index	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L80B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	360 °

Electronic scalability	Yes
Mechanical scalability	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Impact resistance	IK03
IP-rating	IP54
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	Neutral white
PU1, EAN	4007841056117

Sensor-switched LED indoor light

RS PRO P3 S


Neutral white

EAN 4007841 056117

Article number 056117




Detection Zone




Mögliche Montagehöhe: 2,00 m – 4,00 m
Orange: radial und tangential

Dimension Drawing




Light Distribution Curve



Output	18,4 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Luminous flux	2188 lm
Colour temperature	4000 K
Colour Rendering Index	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

Slave/wireless master interconnection circuit diagram



Sensor-switched LED indoor light

RS PRO P3 S

Neutral white

EAN 4007841 056117

Article number 056117



Master/master interconnection circuit diagram

