

Photo-cell-controlled light

L 710 N

Anthracite

EAN 4007841 053161

Article number 053161



3000 K

3000K
warm-white



Twilight switch



IP44



soft light start



energy saving

3 years

manufacturer's
warranty
steinel.de/garantie3y



CE



TüV Nord GS



Light source not
exchangeable



Control gear not
exchangeable

Function description

Beautiful light in pure form. Quite simply, the attractive outdoor light without motion detector always cuts a fine figure whether ON or OFF. The L 710 N is made of UV-resistant plastic and features a modern aluminium designer-style element. The warm-white light (3000 K) sets off building walls with absolute competence. With photo-cell controller, automatic lighting at night and optional night-economy mode. Available in anthracite.

L 710 N

Anthracite

EAN 4007841 053161

Article number 053161

Technical specifications

Dimensions (L x W x H)	140 x 260 x 63 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	Light sensor
Output	8,3 W
Interconnection	No
Slave modeselectable	No
Lichtstrom Gesamtprodukt	729 lm
Stroboskop-Effekt (SVM)	1,5 SVM
Efficiency	88 lm/W
Gesamtprodukt Effizienz	88 lm/W
Colour temperature	3000 K
Colour Rendering Index	= 82
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
LED life expectancy (25 °C)	> 60000 h
Life expectancy of power supply unit (25 °C)	> 60000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Capability of masking out individual segments	No

Electronic scalability	No
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Basic light level function	No
Functions	Light sensor
Soft light start	Yes
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Einstellungen via: Connect Bluetooth Mesh	Potentiometers
With remote control	No
Installation site	wall
Cover material	sticker
Version	Anthracite
PU1, EAN	4007841053161

Dimension Drawing

